


SKR 67F



Fast Recovery Rectifier Diode

SKR 67F

Features

- CAL-Diode (controlled axial lifetime technology), patent no. DE 431044
- Very short recovery time
- Soft recovery under all conditions
- 600 V reverse voltage
- Epoxy meets UL 94V-0 flammability classification





Typical Applications


- Inverse diode for power transistor
- Inverter, UPS
- Snubber and clamping diode

V_{RSM} V	V_{RRM} V	$I_{FRMS} = 105\text{ A}$ (maximum value for continuous operation) $I_{FAV} = 67\text{ A}$ (sin. 180; 50 Hz; $T_c = 85\text{ °C}$)		
600	600	SKR 67F06		

Symbol	Conditions	Values	Units
I_{FAV}	sin. 180; $T_c = 85\text{ (100) °C}$	67 (58)	A
I_{FSM}	$T_{vj} = 25\text{ °C}$; 10 ms $T_{vj} = 150\text{ °C}$; 10 ms	650 580	A A
i^2t	$T_{vj} = 25\text{ °C}$; 8,3 ... 10 ms $T_{vj} = 150\text{ °C}$; 8,3 ... 10 ms	2100 1700	A ² s A ² s
V_F	$T_{vj} = 25\text{ °C}$; $I_F = 75\text{ A}$	max. 1,7	V
$V_{(TO)}$	$T_{vj} = 150\text{ °C}$	0,9	V
r_T	$T_{vj} = 150\text{ °C}$	11	mΩ
I_{RD}	$T_{vj} = 25\text{ °C}$; $V_{RD} = V_{RRM}$	max. 0,2	mA
I_{RD}	$T_{vj} = 125\text{ °C}$; $V_{RD} = V_{RRM}$	max. 4	mA
Q_{rr}	$T_{vj} = 125\text{ °C}$; $I_F = 75\text{ A}$, -di/dt = 800 A/μs, $V_R = 300\text{ V}$	6	μC
I_{RM}		53	A
t_{rr}		250	ns
E_{rr}		-	mJ
$R_{th(j-c)}$		0,35	K/W
$R_{th(c-s)}$		0,25	K/W
T_{vj}		- 40 ... + 150	°C
T_{stg}		- 40 ... + 150	°C
V_{isol}		-	V~
M_s	to heatsink	0,7 ... 1	Nm
a			m/s ²
m	approx.	5	g
Case		E 40	







This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.